



TP-Link Omada EAP783 punto de acceso inalámbrico 19000 Mbit/s Blanco Energía sobre Ethernet (PoE)

Marca : TP-Link

Familia de productos: Omada **Código del producto:** EAP783

Nombre del producto :
EAP783

TP-Link Omada EAP783. 2,4 GHz, 5 GHz, 6 GHz, Rango máximo de transferencia de datos: 19000 Mbit/s. Algoritmos de seguridad soportados: WPA, WPA2, WPA3. Ethernet LAN, velocidad de transferencia de datos: 10000 Mbit/s. Energía sobre Ethernet (PoE). Color del producto: Blanco



Características		Seguridad	
2,4 GHz *	✓	Lista de Control de Acceso (ACL)	✓
5 GHz *	✓	Puertos e Interfaces	
6 GHz *	✓	Ethernet LAN (RJ-45) cantidad de puertos *	2
Rango máximo de transferencia de datos *	19000 Mbit/s	Enchufe de entrada de CC	✓
Velocidad máxima de transferencia de datos (2,4 GHz)	1376 Mbit/s	Control de energía	
Velocidad máxima de transferencia de datos (5 GHz)	5760 Mbit/s	Energía sobre Ethernet (PoE) *	✓
Velocidad máxima de transferencia de datos (6 GHz)	11520 Mbit/s	Rango de voltaje DC	12 V
Ethernet LAN, velocidad de transferencia de datos	10000 Mbit/s	Diseño	
Frecuencia de banda	2.4 - 6 GHz	Ubicación *	Techo, Pared
Estándares de red	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n	Color del producto *	Blanco
		Botón de restaurar	✓
Número de usuarios	760 usuario(s)	Indicadores LED	✓
Selección automática de canal	✓	Antena	
Escáner automático de canales	✓	Tipo de antena *	Interno
MIMO	✓	Peso y dimensiones	
Tipo MIMO	Multi User MIMO	Ancho	280 mm
Soporte VLAN	✓	Profundidad	280 mm
Limitar tasa	✓	Altura	46,5 mm
Soporte de control de flujo	✓	Empaquetado	
Band steering (optimización de rendimiento)	✓	Tipo de embalaje	Caja
Equidad de conexión (ATF)	✓	Contenido del embalaje	
Calidad de servicio (QoS) soporte	✓	Cantidad por paquete	1 pieza(s)
		Kit de montaje	✓
		Guía de configuración rápida	✓

Características		Condiciones ambientales	
BeamForming (conformación de haces)	✓	Intervalo de humedad relativa para funcionamiento	10 - 90%
Seguridad		Intervalo de temperatura operativa	0 - 40 °C
Algoritmos de seguridad soportados *	WPA, WPA2, WPA3	Intervalo de temperatura de almacenaje	-40 - 70 °C
		Intervalo de humedad relativa durante almacenaje	5 - 90%



0840030710070



840030710070



4895252503517

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.