




TP-Link Omada EAP725-Wall 5012 Mbit/s Blanco Energía sobre Ethernet (PoE)

Marca : TP-Link

Familia de productos: Omada **Código del producto:** EAP725-WALL

Nombre del producto :
EAP725-Wall

TP-Link Omada EAP725-Wall. 2,4 GHz, 5 GHz, Rango máximo de transferencia de datos: 5012 Mbit/s. Algoritmos de seguridad soportados: WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal. Ethernet LAN, velocidad de transferencia de datos: 10,100,1000,2500 Mbit/s. Energía sobre Ethernet (PoE). Color del producto: Blanco. Consumo de energía (max): 17 W



Características		Diseño	
2,4 GHz *	✓	Ubicación *	Techo, Pared
5 GHz *	✓	Color del producto *	Blanco
6 GHz *	✗	Botón de restaurar	✓
Rango máximo de transferencia de datos *	5012 Mbit/s	Indicadores LED	✓
Velocidad máxima de transferencia de datos (2,4 GHz)	688 Mbit/s	Antena	
Velocidad máxima de transferencia de datos (5 GHz)	2882 Mbit/s	Tipo de antena *	Interno
Ethernet LAN, velocidad de transferencia de datos	10,100,1000,2500 Mbit/s	Cantidad de antenas	4
Estándares de red	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n, IEEE 802.3at	Ganancia de la antena (max)	5 dBi
Número de usuarios	250 usuario(s)	Desempeño	
Soporte VLAN	✓	Sistemas operativos compatibles	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows 11, Linux
Equidad de conexión (ATF)	✓	Aprobaciones reguladoras	
BeamForming (conformación de haces)	✓	Certificación	FCC, RoHS
Seguridad		Peso y dimensiones	
Algoritmos de seguridad soportados *	WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal	Ancho	86 mm
MAC, filtro de direcciones	✓	Profundidad	40 mm
Número de SSID admitidos	16	Altura	143 mm
Servicio de autenticación remota de llamadas de usuarios (RADIUS)	✓	Empaquetado	
Lista de Control de Acceso (ACL)	✓	Tipo de embalaje	Caja
		Contenido del embalaje	
		Cantidad por paquete	1 pieza(s)
		Kit de montaje	✓
		Condiciones ambientales	
		Intervalo de humedad relativa para funcionamiento	10 - 90%

Puertos e Interfaces		Condiciones ambientales	
Ethernet LAN (RJ-45) cantidad de puertos *	3	Intervalo de temperatura operativa	0 - 40 °C
Control de energía		Intervalo de temperatura de almacenaje	-40 - 70 °C
Energía sobre Ethernet (PoE) *	✓	Intervalo de humedad relativa durante almacenaje	5 - 90%
Consumo de energía (max)	17 W		



8885020626353



1210002607582



0810142823173



810142823173

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.