



Dahua Technology DH-XVR4232AN-I videograbador digital Negro

Marca : Dahua Technology

Código del producto: DH-XVR4232AN-I

Nombre del producto : DH-XVR4232AN-I

Dahua Technology DH-XVR4232AN-I. Color del producto: Negro, Máxima resolución de video: 1920 x 1080 Píxeles, Formatos de compresión de video: H.264, H.264+, H.265, H.265+. Tipo de interfaz ethernet: Ethernet rápido, Protocolos de red compatibles: HTTP; HTTPS; TCP / IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P. Interfaz del HDD: SATA, Capacidad máxima del HDD: 16 TB. Tipo de fuente de alimentación: CC, Tensión CC: 12 V, Consumo energético: 12 W. Ancho: 375 mm, Profundidad: 289,4 mm, Altura: 53 mm

Desempeño		Puertos e Interfaces	
Máxima resolución de video	1920 x 1080 Píxeles	Puertos RS-485	1
Formatos de compresión de video	H.264, H.264+, H.265, H.265+	Conexión	
Formatos de audio soportados	G.711 A-law, G.711 μ-law, PCM	Ethernet	✓
Función de copia de seguridad	✓	Tipo de interfaz ethernet	Ethernet rápido
Detección de pérdida de video	✓	Ethernet LAN (RJ-45) cantidad de puertos	1
Detección de movimiento en video	✓	Protocolos de red compatibles	HTTP; HTTPS; TCP / IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P
Cantidad de canales	32 canales	Disco duro	
Color del producto *	Negro	Número de HDDs soportados	2
Modo de reproducción	Event, General, Instantáneo, Smart, Tag	Interfaz del HDD	SATA
Sistema operativo instalado	LINUX embebido	Capacidad máxima del HDD	16 TB
Canales de entrada de audio	1 canales	Control de energía	
Canales de salida de audio	1.0 canales	Tipo de fuente de alimentación	CC
Velocidad máxima de cuadro	30 pps	Tensión CC	12 V
Modo multipantalla	1, 4, 8, 9, 16, 25, 36	Consumo energético	12 W
Capacidad del rack	1U	Peso y dimensiones	
Certificación	CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2, EN 61000-3-3, EN 55032, EN 50130, EN 55024 FCC: Part 15 Subpart B	Ancho	375 mm
		Profundidad	289,4 mm
		Altura	53 mm
		Peso	1,92 kg
		Empaquetado	
		Ancho del paquete	433 mm
		Profundidad del paquete	366 mm
		Altura del paquete	141 mm
		Peso del paquete	3,01 kg
		Condiciones ambientales	
		Intervalo de temperatura operativa	-10 - 55 °C
		Intervalo de humedad relativa para funcionamiento	0 - 90%

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.