



Dahua Technology XVR5116HS-I3/T videograbador digital Negro

Marca : Dahua Technology

Código del producto: XVR5116HS-I3/T

Nombre del producto : XVR5116HS-I3/T

Dahua Technology XVR5116HS-I3/T. Color del producto: Negro, Máxima resolución de video: 3840 x 2160 Píxeles, Formatos de compresión de video: H.264, H.264+, H.265, H.265+. Entrada de audio: 1 RCA, Salida de audio: 1 RCA, Entrada de vídeo: HDCVI/AHD/TVI/CVBS/IP. Tipo de interfaz ethernet: Ethernet rápido, Protocolos de red compatibles: HTTP, HTTPS, TCP / IP, IPv4, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, P2P. Interfaz del HDD: SATA, Capacidad máxima del HDD: 16 TB. Tipo de fuente de alimentación: CC, Tensión CC: 12 V

Desempeño		Puertos e Interfaces	
Máxima resolución de video	3840 x 2160 Píxeles	Salida de audio	1 RCA
Formatos de compresión de video	H.264, H.264+, H.265, H.265+	Cantidad de puertos USB 2.0	1
Formatos de audio soportados	G.711 A-law, G.711 µ-law, PCM	Cantidad de puertos tipo A USB 3.2 Gen 1 (3.1 Gen 1)	1
Función de copia de seguridad	✓	Entrada de vídeo	HDCVI/AHD/TVI/CVBS/IP
Vídeo capturar velocidad (PAL)	25 pps	Puertos RS-485	1
Vídeo capturar velocidad (NTSC)	30 pps	Conexión	
Detección de pérdida de video	✓	Ethernet	✓
Detección de movimiento en video	✓	Tipo de interfaz ethernet	Ethernet rápido
Cantidad de canales	16 canales	Ethernet LAN (RJ-45) cantidad de puertos	1
Color del producto *	Negro	Protocolos de red compatibles	HTTP, HTTPS, TCP / IP, IPv4, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, P2P
Señal analógica	NTSC, PAL	Disco duro	
Sistema operativo instalado	LINUX embebido	Interfaz del HDD	SATA
Emisión de vídeo	✓	Capacidad máxima del HDD	16 TB
Compatible con transmisión dual	✓	Control de energía	
Tasa de bits	32 Kbit/s	Tipo de fuente de alimentación	CC
Control PTZ	✓	Tensión CC	12 V
Capacidad del rack	1U	Peso y dimensiones	
Certificación	CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2, EN 61000-3-3, EN 55032, EN 50130, EN 55024 FCC: Part 15 Subpart B	Ancho	260 mm
Puertos e Interfaces		Profundidad	237,4 mm
puertos de entrada BNC	16	Altura	47,6 mm
Número de puertos HDMI	1	Peso	1,17 kg
Puertos de salida VGA (D-Sub)	1	Empaquetado	
Entrada de audio	1 RCA	Ancho del paquete	89 mm
		Profundidad del paquete	333 mm
		Altura del paquete	315 mm
		Condiciones ambientales	
		Intervalo de temperatura operativa	-10 - 55 °C
		Intervalo de humedad relativa para funcionamiento	10 - 90%

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.