

Epson C11CF39201 impresora de matriz de punto 550 caracteres por segundo

Marca : Epson

Código del producto: C11CF39201

Nombre del producto : C11CF39201

Epson C11CF39201. Máxima velocidad de impresión: 550 caracteres por segundo, Tamaño de caracteres: 10 caracteres por pulgada, Código de barras incorporado: Code 128 (A/B/C), Code 39, EAN13, EAN8, Interleaved 2/5, POSTNET, UPC-A, UPC-E. Tipos de papel: Sobres, Etiquetas, Papel normal, Rodillo, Cortar rango de espesores de lámina: 0,065 - 0,49 mm, papel continuo rango de espesor: 0,065 - 0,49 mm. Color del producto: Negro, Tamaño de buffer: 128 KB, Nivel de presión acústica (impresión): 55 dB. Interfaz estándar: Paralelo, USB 2.0. Cabezal de impresora: 24-pin, Durabilidad del cabezal de impresión: 400 millón de caracteres, Duración de banda: 5 millón de caracteres



Velocidad de la impresión		Resistencia	
Máximo ancho de impresión (columnas) *	80	Durabilidad del cabezal de impresión	400 millón de caracteres
Color *	×	Duración de banda	5 millón de caracteres
Máxima velocidad de impresión *	550 caracteres por segundo	Tiempo medio entre fallos	25000 h
Tamaño de caracteres	10 caracteres por pulgada	Control de energía	
Código de barras incorporado	Code 128 (A/B/C), Code 39, EAN13, EAN8, Interleaved 2/5, POSTNET, UPC-A, UPC-E	Voltaje de entrada AC	100 - 240 V
conjuntos de caracteres	ISO 8859-15, Italic, PC437, PC850, PC858, Roman 8	Frecuencia de entrada AC	50 - 60 Hz
Dirección de papel		Condiciones ambientales	
Tipos de papel	Sobres, Etiquetas, Papel normal, Rodillo	Intervalo de temperatura operativa	5 - 35 °C
Cortar rango de espesores de lámina	0,065 - 0,49 mm	Intervalo de humedad relativa para funcionamiento	10 - 80%
papel continuo rango de espesor	0,065 - 0,49 mm	Requisitos del sistema	
Características		Sistema operativo Windows soportado	✓
Color del producto *	Negro	Peso y dimensiones	
Tamaño de buffer *	128 KB	Ancho	437 mm
Nivel de presión acústica (impresión) *	55 dB	Profundidad	375 mm
Puertos e Interfaces		Altura	177 mm
Interfaz estándar *	Paralelo, USB 2.0	Peso	7,2 kg
Resistencia		Detalles técnicos	
Cabezal de impresora *	24-pin	Número de pines	24
		Certificados de sostenibilidad	ENERGY STAR



0010343941557



010343941557

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.