



APC BX1000M-LM60 sistema de alimentación ininterrumpida (UPS) Línea interactiva 1 kVA 600 W 8 salidas AC

Marca : APC

Código del producto: BX1000M-LM60

Nombre del producto : BX1000M-LM60

APC BX1000M-LM60. Topología UPS: Línea interactiva, Capacidad de potencia de salida (VA): 1 kVA, Potencia de salida: 600 W. Tipo de salida AC: NEMA 5-15R, Conector: NEMA 5-15P, Cantidad de salidas AC: 8 salidas AC. Vida útil de la batería (máx.): 5 año(s), Tiempo de recarga de la batería: 12 h. Factor de forma: Compacto, Color del producto: Negro, Longitud de cable: 1,83 m. Certificación: FCC Part 15 Class B, NOM, TUV C-US certified



Características		Batería	
Topología UPS *	Línea interactiva	Vida útil de la batería (máx.)	5 año(s)
Capacidad de potencia de salida (VA) *	1 kVA	Tiempo de recarga de la batería	12 h
Potencia de salida *	600 W	Diseño	
Forma de onda *	Seno	Factor de forma *	Compacto
Voltaje de entrada de operación (min) *	88 V	Longitud de cable	1,83 m
Voltaje de entrada de operación (max) *	139 V	Color del producto *	Negro
Frecuencia de entrada *	60 Hz	Tipo de visualizador	LCD
Voltaje de operación de salida (min)	120 V	Condiciones ambientales	
Voltaje de operación de salida (max)	120 V	Intervalo de temperatura operativa	0 - 40 °C
Frecuencia de salida	60 Hz	Intervalo de temperatura de almacenaje	-15 - 45 °C
Máxima corriente	15 A	Intervalo de humedad relativa para funcionamiento	0 - 95%
Índice de aumento de energía	1103 J	Intervalo de humedad relativa durante almacenaje	0 - 95%
Tiempo de respuesta	8 ms	Altitud de funcionamiento	0 - 3000 m
Nivel de ruido	45 dB	Altitud no operativa	0 - 15000 m
Alarma(s) audibles	✓	Aprobaciones reguladoras	
Modos de alarma audibles	Suena una alarma cuando cambia a la batería, Alarma de batería baja, Alarma de sobrecarga	Certificación	FCC Part 15 Class B, NOM, TUV C-US certified
Puertos e Interfaces		Peso y dimensiones	
Tipo de salida AC	NEMA 5-15R	Ancho	91 mm
Conector	NEMA 5-15P	Profundidad	310 mm
Cantidad de salidas AC	8 salidas AC	Altura	190 mm
Puerto USB	✓	Peso	3,27 kg
Ethernet LAN (RJ-45) cantidad de puertos	2	Empaquetado	
Tecnología de cableado	10/100/1000Base-T(X)	Ancho del paquete	142 mm
		Profundidad del paquete	422 mm

Empaquetado

Altura del paquete	253 mm
Peso del paquete	8 kg

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.