



APC SRV2KRARK sistema de alimentación ininterrumpida (UPS) Doble conversión (en línea) 2 kVA 1600 W 4 salidas AC

Marca : APC

Código del producto: SRV2KRARK

Nombre del producto : SRV2KRARK



APC SRV2KRARK. Topología UPS: Doble conversión (en línea), Capacidad de potencia de salida (VA): 2 kVA, Potencia de salida: 1600 W. Tipo de salida AC: NEMA 5-20R, Conector: NEMA L5-20P, Cantidad de salidas AC: 4 salidas AC. Tecnología de batería: Sealed Lead Acid (VRLA), Tiempo de recarga de la batería: 4 h. Factor de forma: Montaje en rack o Montaje en bastidor, Color del producto: Negro, Capacidad del rack: 2U. Certificación: CE, IEC 62040-1-1, IEC 62040-1-2



Características		Diseño	
Topología UPS *	Doble conversión (en línea)	Factor de forma *	Montaje en rack o Montaje en bastidor
Capacidad de potencia de salida (VA) *	2 kVA	Capacidad del rack	2U
Potencia de salida *	1600 W	Longitud de cable	1,5 m
Forma de onda *	Seno	Tipo de enfriamiento	Activo
Voltaje de entrada de operación (min) *	50 V	Ventilador integrado	✓
Voltaje de entrada de operación (max) *	150 V	Color del producto *	Negro
Frecuencia de entrada *	40/70 Hz	Tipo de visualizador	LCD
Voltaje de operación de salida (min)	110 V	Código IP (International Protection)	IP20
Voltaje de operación de salida (max)	115 V	Condiciones ambientales	
Frecuencia de salida	50/60 Hz	Intervalo de temperatura operativa	0 - 40 °C
Índice de aumento de energía	600 J	Intervalo de temperatura de almacenaje	-20 - 50 °C
Eficiencia	88%	Intervalo de humedad relativa para funcionamiento	0 - 95%
Factor de cima	3:1	Altitud de funcionamiento	0 - 3048 m
Nivel de ruido	50 dB	Altitud no operativa	0 - 15240 m
Alarma(s) audibles	✓	Aprobaciones reguladoras	
Modos de alarma audibles	Alarma de batería baja, Alarma de sobrecarga	Certificación	CE, IEC 62040-1-1, IEC 62040-1-2
Puertos e Interfaces		Contenido del embalaje	
Tipo de salida AC	NEMA 5-20R	Estante de montaje	✓
Conector	NEMA L5-20P	Peso y dimensiones	
Cantidad de salidas AC	4 salidas AC	Ancho	437 mm
Puerto USB	✓	Profundidad	462 mm
Cantidad de puertos USB 2.0	1	Altura	86 mm
Puerto - RS-232	1	Peso	18,2 kg
SmartSlot	✓		

Batería		Empaquetado	
Tecnología de batería	Sealed Lead Acid (VRLA)	Ancho del paquete	551 mm
Tiempo de recarga de la batería	4 h	Profundidad del paquete	700 mm
		Altura del paquete	218 mm
		Peso del paquete	20,7 kg

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.