



APC SMX1000C sistema de alimentación ininterrumpida (UPS) Línea interactiva 1 kVA 900 W 8 salidas AC

Marca : APC


Código del producto: SMX1000C

Nombre del producto : SMX1000C

APC SMX1000C. Topología UPS: Línea interactiva, Capacidad de potencia de salida (VA): 1 kVA, Potencia de salida: 900 W. Tipo de salida AC: NEMA 5-15R, Cantidad de salidas AC: 8 salidas AC. Tecnología de batería: Sealed Lead Acid (VRLA), Tiempo de recarga de la batería: 3 h, Cartucho para batería de repuesto: CURK116-01-02. Factor de forma: Montaje en rack/Torre o Montaje en bastidor/Torre, Color del producto: Negro, Longitud de cable: 2,4 m. Ancho: 89 mm, Profundidad: 490 mm, Altura: 432 mm



Características		Batería	
Topología UPS *	Línea interactiva	Tiempo de recarga de la batería	3 h
Capacidad de potencia de salida (VA) *	1 kVA	Cartucho para batería de repuesto	CURK116-01-02
Potencia de salida *	900 W	Diseño	
Forma de onda *	Seno	Factor de forma *	Montaje en rack/Torre o Montaje en bastidor/Torre
Voltaje de entrada de operación (min) *	82 V	Longitud de cable	2,4 m
Voltaje de entrada de operación (max) *	143 V	Color del producto *	Negro
Frecuencia de entrada *	50/60 Hz	Tipo de visualizador	LCD
Voltaje de operación de salida (min)	120 V	Condiciones ambientales	
Voltaje de operación de salida (max)	120 V	Intervalo de temperatura operativa	0 - 40 °C
Máxima corriente	12 A	Intervalo de temperatura de almacenaje	-15 - 45 °C
Índice de aumento de energía	600 J	Intervalo de humedad relativa para funcionamiento	0 - 95%
Nivel de ruido	40 dB	Intervalo de humedad relativa durante almacenaje	0 - 95%
Alarma(s) audibles	✓	Altitud de funcionamiento	0 - 3048 m
Modos de alarma audibles	Alarma de batería baja, Alarma de sobrecarga	Altitud no operativa	0 - 15240 m
Puertos e Interfaces		Peso y dimensiones	
Tipo de salida AC	NEMA 5-15R	Ancho	89 mm
Cantidad de salidas AC	8 salidas AC	Profundidad	490 mm
Puerto USB	✓	Altura	432 mm
Puerto serial	1	Peso	22,9 kg
Dispositivo de apagado de emergencia	✓	Empaquetado	
SmartSlot	✓	Ancho del paquete	246 mm
Batería		Profundidad del paquete	620 mm
Tecnología de batería	Sealed Lead Acid (VRLA)	Altura del paquete	589 mm
		Peso del paquete	27,3 kg



0731304401124



731304401124

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.