



APC SRT5KXLT sistema de alimentación ininterrumpida (UPS) Doble conversión (en línea) 5 kVA 4250 W 4 salidas AC

Marca : APC

Código del producto: SRT5KXLT

Nombre del producto : SRT5KXLT

APC SRT5KXLT. Topología UPS: Doble conversión (en línea), Capacidad de potencia de salida (VA): 5 kVA, Potencia de salida: 4250 W. Tipo de salida AC: NEMA L6-20R, NEMA L6-30R, Conector: NEMA L6-30P, Cantidad de salidas AC: 4 salidas AC. Tecnología de batería: Sealed Lead Acid (VRLA), Tiempo de recarga de la batería: 1,50 h. Factor de forma: Compacto, Color del producto: Negro, Longitud de cable: 3,05 m. Certificados de conformidad: RoHS, Certificación: CSA, FCC, NOM, UL



Características		Batería	
Topología UPS *	Doble conversión (en línea)	Tiempo de recarga de la batería	1,50 h
Capacidad de potencia de salida (VA) *	5 kVA	Diseño	
Potencia de salida *	4250 W	Factor de forma *	Compacto
Forma de onda *	Seno	Longitud de cable	3,05 m
Voltaje de entrada de operación (min) *	160 V	Color del producto *	Negro
Voltaje de entrada de operación (max) *	275 V	Tipo de visualizador	LCD
Frecuencia de entrada *	40/70 Hz	Indicadores LED	✓
Voltaje de operación de salida (max)	240 V	Condiciones ambientales	
Frecuencia de salida	50/60 Hz	Intervalo de temperatura operativa	0 - 40 °C
Índice de aumento de energía	480 J	Intervalo de humedad relativa para funcionamiento	0 - 95%
Factor de cima	3:1	Altitud de funcionamiento	0 - 3000 m
Apagado de emergencia	✓	Altitud no operativa	0 - 15000 m
Salida de voltaje Distorsión Armónica Total	2%	Aprobaciones reguladoras	
Nivel de ruido	55 dB	Certificados de conformidad	RoHS
Alarma(s) audibles	✓	Certificación	CSA, FCC, NOM, UL
Puertos e Interfaces		Sostenibilidad	
Tipo de salida AC	NEMA L6-20R, NEMA L6-30R	Certificados de sostenibilidad	ENERGY STAR
Conector	NEMA L6-30P	Peso y dimensiones	
Cantidad de salidas AC	4 salidas AC	Ancho	130 mm
Cantidad de puertos USB 2.0	1	Profundidad	719 mm
Puerto serial	1	Altura	432 mm
		Peso	55,8 kg

Puertos e Interfaces		Empaquetado	
Ethernet LAN (RJ-45) cantidad de puertos	1	Ancho del paquete	610 mm
Batería		Profundidad del paquete	960 mm
		Altura del paquete	330 mm
Tecnología de batería	Sealed Lead Acid (VRLA)	Peso del paquete	64,4 kg
Datos logísticos			
		Cantidad por palé	6 pieza(s)



0731304301622



731304301622

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.