

## CyberPower LCD CP1350AVRLCDA sistema de alimentación ininterrumpida (UPS) Línea interactiva 1,35 kVA 815 W

**Marca :** CyberPower

**Familia de productos:** LCD

**Código del producto:**  
CP1350AVRLCDA

**Nombre del producto :**  
CP1350AVRLCDA

CyberPower LCD CP1350AVRLCDA. Topología UPS: Línea interactiva, Capacidad de potencia de salida (VA): 1,35 kVA, Potencia de salida: 815 W. Tecnología de batería: Sealed Lead Acid (VRLA), Tiempo de recarga de la batería: 8 h. Factor de forma: Torre, Color del producto: Negro, Material de la carcasa: Plástico. Certificación: FCC Clase B, UL, NOM. Ancho: 100 mm, Profundidad: 348 mm, Altura: 249 mm



| Características                         |                         | Batería                                           |                      |
|-----------------------------------------|-------------------------|---------------------------------------------------|----------------------|
| Topología UPS *                         | Línea interactiva       | Tiempo de recarga de la batería                   | 8 h                  |
| Capacidad de potencia de salida (VA) *  | 1,35 kVA                | <b>Diseño</b>                                     |                      |
| Potencia de salida *                    | 815 W                   | Factor de forma *                                 | Torre                |
| Forma de onda *                         | Seno                    | Material de la carcasa                            | Plástico             |
| Voltaje de entrada de operación (min) * | 90 V                    | Tipo de enfriamiento                              | Pasivo               |
| Voltaje de entrada de operación (max) * | 139 V                   | Color del producto *                              | Negro                |
| Frecuencia de entrada *                 | 60 Hz                   | Tipo de control                                   | Botones              |
| Regulación automática de voltaje (AVR)  | ✓                       | Tipo de visualizador                              | LCD                  |
| Máxima corriente                        | 12 A                    | Indicadores LED                                   | ✓                    |
| Protección de sobrecarga                | ✓                       | <b>Condiciones ambientales</b>                    |                      |
| Alarma(s) audibles                      | ✓                       | Intervalo de temperatura operativa                | 0 - 40 °C            |
| <b>Puertos e Interfaces</b>             |                         | Intervalo de humedad relativa para funcionamiento | 0 - 95%              |
| Puerto serial                           | 1                       | <b>Aprobaciones reguladoras</b>                   |                      |
| <b>Batería</b>                          |                         | Certificación                                     | FCC Clase B, UL, NOM |
| Tecnología de batería                   | Sealed Lead Acid (VRLA) | <b>Peso y dimensiones</b>                         |                      |
|                                         |                         | Ancho                                             | 100 mm               |
|                                         |                         | Profundidad                                       | 348 mm               |
|                                         |                         | Altura                                            | 249 mm               |
|                                         |                         | Peso                                              | 10,1 kg              |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.