

## CyberPower OM1500ATLCD sistema de alimentación ininterrumpida (UPS) Línea interactiva 1,5 kVA 8 salidas AC



**Marca :** CyberPower

**Código del producto:** OM1500ATLCD

**Nombre del producto :** OM1500ATLCD

1500VA, 120Vac, 8 x NEMA 5-15R, 4ms, Torre

CyberPower OM1500ATLCD. Topología UPS: Línea interactiva, Capacidad de potencia de salida (VA): 1,5 kVA, Voltaje de entrada de operación (min): 82 V. Tipo de salida AC: NEMA 5-15R, Conector: NEMA 5-15P, Cantidad de salidas AC: 8 salidas AC. Tiempo típico de respaldo a carga completa: 60 min, Tiempo típico de respaldo a media carga: 120 min, Tiempo de recarga de la batería: 8 h. Factor de forma: Torre, Color del producto: Negro, Tipo de enfriamiento: Activo. Ancho: 148 mm, Profundidad: 298 mm, Altura: 178 mm

| Características                          |                   | Batería                                           |                     |
|------------------------------------------|-------------------|---------------------------------------------------|---------------------|
| Topología UPS *                          | Línea interactiva | Tiempo típico de respaldo a carga completa        | 60 min              |
| Capacidad de potencia de salida (VA) *   | 1,5 kVA           | Tiempo típico de respaldo a media carga           | 120 min             |
| Voltaje de entrada de operación (min) *  | 82 V              | Tiempo de recarga de la batería                   | 8 h                 |
| Voltaje de entrada de operación (max) *  | 148 V             | Diseño                                            |                     |
| Frecuencia de entrada *                  | 50/60 Hz          | Factor de forma *                                 | Torre               |
| Voltaje de operación de salida (min)     | 108 V             | Tipo de enfriamiento                              | Activo              |
| Voltaje de operación de salida (max)     | 132 V             | Color del producto *                              | Negro               |
| Índice de aumento de energía             | 245 J             | Tipo de visualizador                              | LCD                 |
| Tiempo de respuesta                      | 4 ms              | Indicadores LED                                   | ✓                   |
| Puertos e Interfaces                     |                   | Condiciones ambientales                           |                     |
| Tipo de salida AC                        | NEMA 5-15R        | Intervalo de temperatura operativa                | 0 - 40 °C           |
| Conector                                 | NEMA 5-15P        | Intervalo de humedad relativa para funcionamiento | 0 - 90%             |
| Cantidad de salidas AC                   | 8 salidas AC      | Peso y dimensiones                                |                     |
| Cantidad de puertos USB 2.0              | 1                 | Ancho                                             | 148 mm              |
| Puertos de módem (RJ-11)                 | 1                 | Profundidad                                       | 298 mm              |
| Ethernet LAN (RJ-45) cantidad de puertos | 1                 | Altura                                            | 178 mm              |
| Batería                                  |                   | Peso                                              | 9,27 kg             |
| Numero de baterías soportadas            | 2                 | Empaquetado                                       |                     |
|                                          |                   | Software incluido                                 | PowerPanel Personal |
|                                          |                   | Otras características                             |                     |
|                                          |                   | Tipo de batería                                   | RBP0089             |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.