



## Dahua Technology PFM350-480-A sistema de alimentación ininterrumpida (UPS) Línea interactiva 0,8 kVA 480 W 2 salidas AC

**Marca :** Dahua Technology

**Código del producto:** DH-PFM350-480-A

**Nombre del producto :** PFM350-480-A

Dahua Technology PFM350-480-A. Topología UPS: Línea interactiva, Capacidad de potencia de salida (VA): 0,8 kVA, Potencia de salida: 480 W. Cantidad de salidas AC: 2 salidas AC. Tecnología de batería: Plomo-ácido, Capacidad de la batería: 9 Ah, Voltaje de la pila: 12 V. Factor de forma: Compacto, Color del producto: Negro, Longitud de cable: 1 m. Certificados de conformidad: CE



| Características                         |                                           | Diseño                                            |           |
|-----------------------------------------|-------------------------------------------|---------------------------------------------------|-----------|
| Topología UPS *                         | Línea interactiva                         | Factor de forma *                                 | Compacto  |
| Capacidad de potencia de salida (VA) *  | 0,8 kVA                                   | Longitud de cable                                 | 1 m       |
| Potencia de salida *                    | 480 W                                     | Color del producto *                              | Negro     |
| Forma de onda *                         | Seno                                      | <b>Condiciones ambientales</b>                    |           |
| Voltaje de entrada de operación (min) * | 150 V                                     | Intervalo de temperatura operativa                | 0 - 40 °C |
| Voltaje de entrada de operación (max) * | 275 V                                     | Intervalo de temperatura de almacenaje            | 0 - 40 °C |
| Frecuencia de entrada *                 | 50/60 Hz                                  | Intervalo de humedad relativa para funcionamiento | 0 - 90%   |
| Voltaje de operación de salida (min)    | 220 V                                     | Intervalo de humedad relativa durante almacenaje  | 0 - 90%   |
| Frecuencia de salida                    | 50/60 Hz                                  | <b>Aprobaciones reguladoras</b>                   |           |
| Factor de poder                         | 0,85                                      | Certificados de conformidad                       | CE        |
| Funciones de protección de poder        | Sobrecarga, Descarga excesiva, Sobrecarga | <b>Peso y dimensiones</b>                         |           |
| Puertos e Interfaces                    |                                           | Ancho                                             | 87 mm     |
| Cantidad de salidas AC                  | 2 salidas AC                              | Profundidad                                       | 335 mm    |
| Batería                                 |                                           | Altura                                            | 143 mm    |
| Tecnología de batería                   | Plomo-ácido                               | Peso                                              | 5 kg      |
| Capacidad de la batería                 | 9 Ah                                      | <b>Empaquetado</b>                                |           |
| Voltaje de la pila                      | 12 V                                      | Ancho del paquete                                 | 169 mm    |
| Corriente de carga                      | 2 A                                       | Profundidad del paquete                           | 417 mm    |
|                                         |                                           | Altura del paquete                                | 234 mm    |
|                                         |                                           | Peso del paquete                                  | 5,6 kg    |
|                                         |                                           | Tipo de embalaje                                  | Caja      |



6923172507730

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.