



Dahua Technology PFS3006-4ET-60 No administrado L2 Fast Ethernet (10/100) Energía sobre Ethernet (PoE) Negro


Marca : Dahua Technology

Código del producto: DH-PFS3006-4ET-60-V2

Nombre del producto : PFS3006-4ET-60

Dahua Technology PFS3006-4ET-60. Tipo de interruptor: No administrado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Fast Ethernet (10/100), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 6. Tabla de direcciones MAC: 2000 entradas, Capacidad de conmutación: 1,8 Gbit/s. Voltaje de entrada DC: 53 V. Conector eléctrico: Toma de entrada de CC. Energía sobre Ethernet (PoE). Montaje de pared

Características de administración		Control de energía	
Tipo de interruptor *	No administrado	Fuente de alimentación incluida *	✓
Capa del interruptor	L2	Voltaje de entrada DC	53 V
Puertos e Interfaces		Alimentación a través de Ethernet (PoE)	
Cantidad de puertos básicos de conmutación RJ-45 Ethernet *	6	Energía sobre Ethernet (PoE) *	✓
Puertos tipo básico de conmutación RJ-45 Ethernet *	Fast Ethernet (10/100)	Cantidad de puertos Power over Ethernet (PoE)	4
Cantidad de puertos Fast Ethernet (cobre)	6	Potencia a través de Ethernet (PoE) Presupuesto	60 W
Conector eléctrico	Toma de entrada de CC	Condiciones ambientales	
Conexión		Intervalo de temperatura operativa	-10 - 55 °C
Soporte 10G *	✗	Intervalo de temperatura de almacenaje	-20 - 70 °C
Auto MDI / MDI-X	✓	Intervalo de humedad relativa para funcionamiento	5 - 95%
Ethernet LAN, velocidad de transferencia de datos	10,100 Mbit/s	Intervalo de humedad relativa durante almacenaje	5 - 95%
Transmisión de datos		Peso y dimensiones	
Capacidad de conmutación *	1,8 Gbit/s	Ancho	130 mm
Tasa de reenvío	0,89 Mpps	Profundidad	85 mm
Tabla de direcciones MAC *	2000 entradas	Altura	26 mm
Memoria intermedia de paquetes	1 MB	Peso	300 g
Diseño		Contenido del embalaje	
Montaje en rack *	✗	Manual de usuario	✓
Apilable *	✗	Empaquetado	
Color del producto	Negro	Ancho del paquete	267 mm
Material de la carcasa	Metal	Profundidad del paquete	239 mm
Indicadores LED	✓	Altura del paquete	77 mm
Montaje de pared	✓	Peso del paquete	900 g
Control de energía			
Fuente de energía *	CC		



6923172500717

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.